

type.1

フランジ式エアモータ性能一覧表

型式	型番	空気圧	最大出力	回転速度	トルク	空気消費量	質量	給気口
	No.	MPa	KW	min ⁻¹	Nm	m ³ /min	kg	RC
M-1/2L	62A	0.5	0.3	2590	1.1	0.8	8	3/8
M-1L	51	0.5	1.0	1950	5.0	1.5	15	1/2
M-1G1F	2	0.5	1.0	1950	4.9	1.4	30	1/2
M-1G2F	-	0.5	0.9	910	9.7	1.4	38	1/2
M-1G11F	-	0.5	0.9	177	49.5	1.5	50	1/2
M-1G16F	1	0.5	1.0	124	74.0	1.4	52	1/2
M-1G20F	1A	0.5	0.9	97	94.0	1.4	50	1/2
M-1G650VFB	2	0.5	0.8	3	2590	1.5	180	1/2
M-2L	51	0.5	1.1	1640	6.6	1.5	16	1/2
M-2G1BF	1	0.5	1.1	1600	6.5	1.5	32	1/2
M-2G16F	1	0.4	0.7	65	100	1.2	42	1/2
M-3L	51	0.5	3.4	1040	31.4	4.0	45	1
M-3G1F	2	0.5	2.9	900	31	4.0	72	1
M-3HG4F	1	0.4	2.3	320	70	4.0	100	1
M-3HG6F	2	0.4	2.5	163	147	4.0	100	1
M-5L	51	0.5	4.1	1030	38	4.8	45	1
M-5HG4F	2	0.5	3.9	253	149	4.8	100	1
M-5HG6F	2	0.5	3.9	176	215	4.8	110	1
M-7L	55A	0.5	5.1	590	83	6.7	75	1
M-10L	51SA	0.5	8.4	650	123	9.2	140	1-1/4
M-10G1F	1	0.5	8.3	650	122	9.2	150	1-1/4
M-18L	51	0.5	11.8	650	174	15.5	145	1-1/4