

type.3 ブレーキ式エアモータ性能一覧表

型式	型番	空気圧	最大出力	回転速度	トルク	空気消費量	質量	給気口
	No.	MPa	KW	min ⁻¹	Nm	m ³ /min	kg	RC
M-1G1B	51D	0.5	1.4	1950	5	1.4	44	1/2
M-1G4B	1D	0.5	1.0	488	20	1.4	48	1/2
M-1G7B	2D	0.5	1.0	304	31	1.4	50	1/2
M-1G16B	1D	0.4	0.7	116	60	1.2	60	1/2
M-1G20B	1	0.5	1.0	95	98	1.4	55	1/2
M-1G650VFB	2	0.5	0.8	3	2590	1.5	180	1/2
M-2G1B	51D	0.5	1.2	1640	7	1.5	37	1/2
M-2G50B	1	0.5	1.1	33	304	1.5	70	1/2
M-2G1500B	1	0.5	0.9	1.1	7780	1.5	450	1/2
M-3HG1B	1A	0.5	3.4	1040	31	4.0	110	1
M-3HG4B	2D	0.5	3.3	256	1244	4.0	143	3/4
M-3HG10B	2	0.5	2.8	85	313	4.1	105	3/4
M-3G50B	-	0.5	2.6	17	1499	4.1	165	3/4
M-5HG1B	-	0.5	4.1	1030	38	4.8	125	1
M-5HG4B	60D	0.4	2.9	241	113	4.0	148	3/4
M-7G1B	10D	0.5	4.9	600	78	6.0	150	1
M-7G8B	1	0.5	5.5	8	637	7.0	200	1
M-7G320VFB	-	0.6	4.9	2.4	19600	9.0	760	1
M-10G3B	1	0.4	5.4	220	235	8.0	300	1-1/4
M-18G1B	-	0.6	14.2	700	193	19.0	330	1-1/4